


1	2	3	4	5	6	7	8
---	---	---	---	---	---	---	---

A



10P/14P/16P无槽

1.MATERIAL SPECIFICATION:
1-1.HOUSING: PBT,UL94V-0
1-2.CONTACTS: BRASS
2.PLATING SPECIFICATION:
2-1.CONTACTS:
TIN/GOLD FLASH PLATED OVER ALL.

3-1.CURRENT RATING: 3A
RATED VOLTAGE : 250V

3-3.INSULATION RESISTANCE: 1000MΩ Min
3-4.DIELECTRIC WITHSTANDING : 1000V AC

4-1.OPERATING TEMPERATURE: $-40^{\circ}\text{C}\sim+105^{\circ}\text{C}$.

6.PACKAGE SPEC: TRAY

The diagram illustrates the structure of a 12-digit part number, with each digit or group of digits corresponding to a specific attribute. The part number is shown as D25530 F 0-2 XX 6 X X X. Lines connect each segment to its description:

- SERIES NO:** D25530
- MALE FEMALE:** F (F-FEMALE)
- ANGLE:** 0-2 (0-180°)
- ROW NO:** 0-2 (2-DOUBLE ROW)
- PIN Q'PY:** XX (10~64)
- TERMIPOINT:** 6 (6-PUNCTURED TYPE)
- TYPE:** X (1-2件套)
- COLOR:** X (J-GREY)
- PLATING:** X (1-G/F)

PIN Q' PY:
10~64

— PLATING:
1—G/F

—TERMPIPOINT:
6—PUNCTURED TYPE

Circuit	Dimensions(mm)			Circuit	Dimensions(mm)		
	A	B	C		A	B	C
10	10.16	17.96	22.70	30	35.56	43.36	48.10
14	15.24	23.04	27.78	34	40.64	48.44	53.18
16	17.78	25.58	30.32	40	48.26	56.06	60.80
20	22.86	30.66	35.40	50	60.96	68.76	73.50
24	27.94	35.74	40.48	60	73.66	81.46	86.20
26	30.48	38.28	43.02	64	78.74	86.54	91.28

REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO: D25530F0-2XX6XXX	DWG.NO: ENDE05	 WanLian Technology Co., Ltd	
AO	NEW RELEASE	22.10.28		LINEAR	ANGLES	APPROVED	Wang_jr	22.10.28				
				0.0±0.35	X*REF±6°							
				UNIT:mm	0.00±0.25	X*±3°	CHECK	XueZe_Ma	22.10.28	TITLE: Pitch 2.54mm 180° 双排 DIP 母座 2件套		
				SIZE: A4	0.000±0.10	X*X' ±2°	DRAWN	LanXuan_Hou	22.10.28			
										REV: AO	SHEET: 1/2	

	1	2	3	4	5	6	7	8						
A	The product using material and processing must conform to the "WI-PZ-001"HSF technical standard control requirements													
	RoHS													
B	Circuit	产品长度	每行包装个数		每盘个数		每屯盒数	每箱个数	重量					
C			266	每行整数	行数	每盘整数 *行数								
	06	17.87	14.89	14	10	140	25	3500						
	08	20.41	13.03	12	10	120	25	3000						
	10	22.95	11.59	11	10	110	25	2750						
D	12	25.49	10.44	10	10	100	25	2500						
	14	28.03	9.49	9	10	90	25	2250						
	16	30.57	8.70	8	10	80	25	2000						
E	20	35.65	7.46	7	10	70	25	1750						
	24	40.73	6.53	6	10	60	25	1500						
	26	43.27	6.15	6	10	60	25	1500						
F	30	48.35	5.50	5	10	50	25	1250						
	34	53.43	4.98	4	10	40	25	1000						
	40	61.05	4.36	4	10	40	25	1000						
	50	73.75	3.61	3	10	30	25	750						
G	60	86.45	3.08	3	10	30	25	750						
	64	91.53	2.91	2	10	20	25	500						
H	REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO: D25530F0-2XX6XXX	DWG.NO: ENDE05	 WanLian Technology Co., Ltd		
	AO	NEW RELEASE	22.10.28		LINEAR	ANGLES	APPROVED	Wang_jr	22.10.28					
				0.0±0.35	X°REF±6°									
					UNIT:mm	0.00±0.25	X°±3°	CHECK	XueZe_Ma	22.10.28	TITLE: 包装规范		REV: A0	SHEET: 2/2
					SIZE: A4	0.000±0.10	X°X' ±2°	DRAWN	LanXuan_Hou	22.10.28				
	1	2	3	4	5	6	7	8						