










1		2		3		4		5		6		7		8	
		The product using material and processing must conform to the "WL-PZ-001"HSF technical standard control requirements				Insulator Coded									
A	Series		2	3	4	5	6	8	12						
	Pin Number														
B	Conductor size(AWG)		22	22	22	22	24	24	26						
	Pin size(mm)		1	1	1	1	0.8	0.8	0.6						
	Rated current (A)		4	4	4	4	2	2	1						
	Rated voltage (V)		250	250	250	60	30	30	30						
C	Technical Characteristics														
D	1. Durability: >500 mate/unmate cycles 2. Rated Temperature: -40℃, +80℃ 3. Waterproof: IP67 4. Connection mode: threaded connection 5. Connection mode: Screw crimping 6. Pollution level: 3 7. Cable diameter: 4~7MM														
E	Material specification														
F	5	Body	PA	BLACK	Pcs	1									
	4	PIN	Copper	G/F	Pcs	2~12									
	3	Screw Cap	Brass	Nickel plated	Pcs	1									
G	2	O-RING	Rubber	/	Pcs	1									
	1	Insulator	PA	BLACK	Pcs	1									
	No.	Specification	Material	Treat	Unit	Q'ty									
H	REV.	REVISION RECORD	DATE	GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO:	DWG.NO:	 WanLian Technology Co., Ltd REV: A0    SHEET: 1/1				
	AO	NEW RELEASE		 LINEAR ANGLES		APPROVED			M12XXX-02-010	ENDE05					
				0.0±0.35 X°REF±6°		DESIGNER			TITLE:						
				0.00±0.25 X°±3°					M12 Packaged female plug PG9						
				0.000±0.10 X°X' ±2°		DRAWN									
1		2		3		4		5		6		7		8	