

1		2		3		4		5		6		7		8									
The product using material and processing must conform to the "WL-PZ-001"HSF technical standard control requirements																							
芯数		2	3	4	5	6	8	绝缘编码 <table><tr><td>编码</td><td>A</td><td>B</td><td>D</td></tr><tr><td>芯数排列</td><td></td><td></td><td></td></tr></table>								编码	A	B	D	芯数排列			
编码	A	B	D																				
芯数排列																							
图形																							
适配线缆 (AWG)		22	22	22	22	24	24																
导体直径 (mm)		1.0	1.0	1.0	1.0	0.8	0.8																
额定电流 (A)		4A	4A	4A	4A	2A	2A																
额定电压 (V)		250V	250V	250V	60V	30V	30V																
绝缘电阻 (MΩ)		≥1000	≥1000	≥1000	≥1000	≥1000	≥1000																
接触电阻 (mΩ)		≤10	≤10	≤10	≤10	≤10	≤10	技术特性 1. 接插次数: ≥500次 2. 额定温度: -40℃, +105℃ 3. 盐雾: >48h 4. 防水等级: IP67 5. 接插方式: 螺纹锁紧 6. 接线方式: 螺钉压接															
材料规格																							
D	密封O型圈	橡胶	黑色	Pcs	1																		
D	屏蔽壳	黄铜	镀镍	Pcs	1																		
C	外壳	黄铜	镀镍	Pcs	1																		
B	接触件	黄铜	镀金	Pcs	2~8																		
A	绝缘体	PA尼龙	黑色	Pcs	1																		
No.	Specification	Material	Treat	Unit	Q'ty																		
REV.	REVISION RECORD		DATE			GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO: M12XXX-08-067	DWG.NO: ENDE05	WanLian Technology Co., Ltd										
A0	NEW RELEASE		25.04.23			LINEAR	ANGLES	APPROVED															
					0.0±0.35	X°REF±6°	DESIGNER			TITLE: M12防水 2~8P线端母头 屏蔽款+10L直纹螺母		REV: A0	SHEET: 1/1										
				UNIT:mm	0.00±0.25	X°±3°																	
				SIZE: A4	0.000±0.10	X°X' ±2°	DRAWN																
1		2		3		4		5		6		7		8									