

The product using material and processing must conform to the "WI-PZ-001"HSF technical standard control requirements

RoHS

30.80±0.38

24.99±0.15

16.35±0.25

12.50

7.90±0.25

7.90±0.25

24.99

2.29

15-φ1.20

1.98

7.04

1.145

1.98

2-φ3.18

#4-40 UNC

13.30

9.80±0.25

0.65

5.85±0.25

19.00±0.25

3.00±0.25

2.60±0.20

10.70±0.38

9.60

1.98

1.98

10.70±0.25

MATERIALS AND FINISH

SHELL : STEEL MATERIAL, TIN FINISHED

INSULATOR : PBT THERMOPLASTIC, 30% GLASS FILLED, BLUE COLOR

CONTACT MATERIAL : BRASS

CONTACT FINISH : SELEVITE GOLD FINISHED

RIVETED INSERT: BRASS MATERIAL , TIN FINISHED

JACK SCREWS : BRASS MATERIAL , NICKEL FINISHED WITH #4-40 THREADED ASSEMBLED

ELECTRICAL CHARACTERISTICS

CONTACT CURRENT RATING : 5.0 AMPS

CONTACT RESISTANCE : 30 MILLIOHMS MAX.

DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC MIN.

INSULATION RESISTANCE : 1000 MEGAOHMS MIN.

TEMPERATURE RATING : -55°C ~ +105°C

P/N: WLDBF0-15 1 X X 0 152

PLATING: 1-G/F

COLOUR: G-BLUE

H	REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO:	DWG.NO:						
	A0	NEW RELEASE	21.01.13		LINEAR	ANGLES	APPROVED	Wang_jr	21.01.13	WLDBF0-151XX0152	ENDE05						
					0.0±0.35	X'REF±6°	DESIGNER	Han_Gao	21.01.13	TITLE: HDS 15F 180°DIP RIVETING COPPER COLUMN 9.80 PIN		REV: A0	SHEET: 1/1				
				UNIT:mm	0.00±0.25	X'±3°	DRAWN	Zijun_Huang	21.01.13								
				SIZE: A4	0.000±0.10	X'X' ±2°											
	1	2	3		4	5	6	7	8								