



The product using material and processing must conform to the "WI-PZ-001" HSF technical standard control requirements



- CHARACTERISTICS:
- 1、 RATED VOLTAGE: 250V AC CD
 - 2、 RATED CURRENT: 3.0AMP
 - 3、 CONTACT RESISTANCE: 30mΩ Max.
 - 4、 INSULATION RESISTANCE: 1000 MΩ MIN. 500V DC
 - 5、 Electric Pressure: Keeping 60 second in AC 500V/1mA
 - 6、 Operating temperature: -55℃~105℃
 - 7、 INSERTION/EXTRACTION FORCE PER CONTACT: 13.2Kg Max
1.1Kg Min.

Specification Type		
A	B	C

ORDER INFORMTION

P/N: WLDBM0-624XXX050

Number of Contact: _____

Contact Type: _____
4: SOLDERING

Plating Contact: _____
1: Gold Flash
3: Au: 3U"
6: Au: 30U"

SCREW: _____

Housing color: _____
A: Black
S: Nature

A: Specification Type A
B: Specification Type B
C: Specification Type C

REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART. NO:	DWG. NO:	 WanLian Teconology Co., Ltd
A0	NEW RELEASE	21.01.13		LINEAR	ANGLES	APPROVED	Wang_jr	21.03.11	WLDBM0-624XXX050	ENDE05	
			0.0±0.35	X° REF±6°	DESIGNER	Ding_Bo	21.03.11	TITLE:			
			UNIT: mm	X° ±3°	DRAWN	Ou_Jian	21.03.11	HDB 62M SOLDERING			
			SIZE: A4	0.000±0.10	X° X'±2°					REV: A0	SHEET: 1/1