

The product using material and processing must conform to the "WI-PZ-001"HSF technical standard control requirements

RoHS

NOTE:

1.MATERIAL:

1.1 HOUSING:PBT, COLOR:BLUE.

1.2 TERMINAL:COPPER ALLOY.

1.3 SHELL:SPCC

1.4 HARPOON:COPPER ALLOY.

2. PLATING:

2.1 CONTACT: SELECTIVE GOLD PLATED ON CONTACT AREA
80u" Min. TIN PLATED ON SOLDER TAIL
50u" Min. NICKEL UNDER-PLATED

2.2 SHELL:50u" Min, NICKEL PLATED OVERALL

2.3 HARPOON:50u" Min, TIN PLATED OVERALL

3. SPECIFICATIONS:

VOLTAGE: 250 VAC(RMS) MAX.

CURRENT RATING: 3 AMPERE PER CONTACT

CONTACT RESISTANCE: 25 MILLIOHMS MAX.

INSULATION RESISTANCE: 5000 MEGOHMS MIN.

DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC(RMS)

OPERATING TEMPEROTURE:-25? ~ +85?

P/N: WLDBM9-15 1 X X 0 138

PLATING: 1-G/F COLOUR: G-BLUE

H	REV.		REVISION RECORD		DATE			GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO:		DWG.NO:	 WanLian Teconology Co., Ltd							
	AO		NEW RELEASE		21.01.13			LINEAR	ANGLES	APPROVED	Wang_jr	21.01.13	WLDBM9-151XX0138		ENDE05								
								0.0±0.35	X°REF±6°														
							UNIT:mm	0.00±0.25	X°±3°	DESIGNER	Han_Gao	21.01.13	TITLE:			REV: A0		SHEET: 1/1					
							SIZE: A4	0.000±0.10	X°X' ±2°	DRAWN	Zijun_Huang	21.01.13	HDR8.89 15M 90°DIP 直锁										
1			2			3			4			5			6			7			8		