




The product using material and processing must conform to the "WI-PZ-001" HSF technical standard control requirements



CHARACTERISTICS:


- 1, RATED VOLTAGE: 250V AC CD
- 2, RATED CURRENT: 3.0AMP
- 3, CONTACT RESISTANCE: 30mΩ Max.
- 4, INSULATION RESISTANCE: 1000 MΩ MIN. 500V DC
- 5, Electric Pressure: Keeping 60 second in AC 500V/1mA
- 6, Operating temperature: -55℃~105℃
- 7, INSERTION/EXTRACTION FORCE PER CONTACT: 8.5Kg Max
0.75Kg Min.



PCB layout

Specification Type (1:2)				
A	B	C	D	E
	4.80	5.80	4.80	5.80

ORDER INFORMATION



REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART. NO:	DWG. NO:	
A0	NEW RELEASE	21.01.13		LINEAR	ANGLES	APPROVED	Wang_jr	21.03.11	WLDBM9-251XXX040	ENDE05	
			UNIT: mm	0.00 ± 0.25	X° ± 3°	DESIGNER	Ding_Bo	21.03.11	TITLE:		REV: A0 SHEET: 1/1
			SIZE: A4	0.000 ± 0.10	X° X' ± 2°	DRAWN	Ou_Jian	21.03.11	DR 25M 8.08 90° DIP		