


The product using material and processing must conform to the "WL-PZ-001" HSF technical standard control requirements

RoHS

图形																		
规格	2PIN	2PIN	2PIN 4改2	3PIN	3PIN	3PIN 4改3	4PIN 2+2	4PIN	5PIN	5PIN 正方形2+3	5PIN 180°	5PIN 260° 2+3	5PIN 360°	6PIN 360°	6PIN 258°	6PIN 8改6	7PIN	8PIN
X值	1.20	1.50	1.00	1.20	1.50	1.00	1.20+1.00	1.00	1.00	1.50+1.00	0.80	1.50+1.00	1.00	1.00	0.80	0.80	0.80	0.80



组合图

Engagemnr firce	≤50N	Rated volage	2-5pin:60v 6-8pin:30v	PARTS	MARERIALS	TREATMENT	AMOUNT	
Disengagement force	≥5N	Rated current	2-5pin:4A 6-8pin:2A					
Mechanical lifespan	≥500	Insulation resirance	≥1000MΩ	A	HOUSING	PA66+GF	SPECIFY COLOR	1
IP rating	IP67/IP68	Conract resistanace	≤10MΩ	B	CONTACT	BRASS	GOLD PLATED	2
Flammability	UL94 V-0	Operation Temperature	-40° C~105° C	C	NUT	ALALLOY	BLACK/SILVER	1
				D	O-RING	EPDM	BLACK	1
				E				

P/N	TITLE	
M12A02-08-072	M12防水 A-CODE 2P线端母头 B款9.0L铝螺母 1.5*2	
REV.	REVISION RECORD	DATE
A0	NEW RELEASE	

GENERAL TOLERANCES	SCALE: 1:1	NAME	DATE	PART.NO:	DWG.NO:
LINEAR				M12A02-08-072	ENDE05
ANGLES					
0.0±0.35					
X'REF±6'					
UNIT:mm				TITLE:	
0.00±0.25				M12防水 A-CODE 2P线端母头 B款9.0L铝螺母 1.5*2	
0.000±0.10					
X'X' ±2'					



REV: A0 SHEET: 1/1