









RoHS



组合图

Engagemnr force	≤50N	Rated volage	50v/63v		PARTS	MARERIALS	TREATMENT	AMOUNT
Disengagement force	≥10N	Rated current	12A	A	HOUSING	PA66+GF	SPECIFY COLOR	1
Mechanical lifespan	≥500	Insulation resistance	≥1000MΩ	B	CONTACT	BRONZE	GOLD PLATED	2~4
IP rating	IP67	Conract resistangce	≤10MΩ	C	NUT	BRASS	NICKL PLATED	1
Flammability	UL94 V-0	Operation Temperature	-40° C~105° C	D				
				E				

REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE	NAME	DATE	PART NO.	DWG NO.	 TERMINAL&CONNECTORS
A0	NEW RELEASE			LINEAR	ANGLES	1:1					
				0.0±0.25	X° REF±6°	APPROVED					
				0.00±0.15	X° ±3°	DESIGNER					
			UNIT: MM	0.00±0.08	X° X' ±2°	DRAWN	TITLE				
			SIZE: A4	0.000±0.08	X° X' ±2°		M12线端成型式 T编码 公头 焊线式 +11.8L 双网纹螺丝				
											REV
											A0
											SHEET
											1/1