








RoHS



Engagemnr force	≤50N	Rated volage	50v/63v		PARTS	MARERIALS	TREATMENT	AMOUNT
Disengagement force	≥10N	Rated current	12A	A	HOUSING	PA66+GF	SPECIFY COLOR	1
Mechanical lifespan	≥500	Insulation resistance	≥1000MΩ	B	CONTACT	BRONZE	GOLD PLATED	2~4
IP rating	IP67	Conract resistangce	≤10MΩ	C	NUT	BRASS	NICKL PLATED	1
Flammability	UL94 V-0	Operation Temperature	-40° C~105° C	D	O-RING	EPDM	BLACK	1
				E				

REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE	NAME	DATE	PART NO.	DWG NO.	 <b>TERMINAL&amp;CONNECTORS</b>					
A0	NEW RELEASE			LINEAR	ANGLES	1:1										
				0.0±0.25	X° REF±6°	APPROVED										
				UNIT: MM	0.00±0.15	X° ±3°									DESIGNER	
			SIZE: A4	0.000±0.08	X° X' ±2°	DRAWN	TITLE									
									M12TX-08-107				ENDE05			
									M12线端成型式 T编码 母头 焊线式 +10.5L 网纹螺母							
									REV	A0	SHEET	1/1				