
















	1	2	3	4	5	6	7	8																																								
The product using material and processing must conform to the "WI-PZ-001"HSF technical standard control requirements																																																
A	pin位 X 值	2pin 1.00	3pin 1.00	4pin 1.00	5pin 1.00	6pin 0.80	7pin 0.80	8pin 0.80																																								
B	A-CODE 图 形																																															
C	B-CODE 图 形																																															
D	D-CODE 图 形																																															
E																																																
F							<table><tr><td></td><td>PARTS</td><td>MATERIALS</td><td>TREATMENT</td><td>AMOUNT</td></tr><tr><td>A</td><td>HOUSING</td><td>PA66+GF</td><td>SPECIFY COLOR</td><td>1+1</td></tr><tr><td>B</td><td>CONTACT</td><td>BRASS</td><td>GOLD PLATED</td><td>2~8</td></tr><tr><td>C</td><td>OUTER CONTACT</td><td>BRASS</td><td>NICKL PLATED</td><td>1</td></tr><tr><td>D</td><td>NUT</td><td>BRASS</td><td>NICKL PLATED</td><td>3</td></tr><tr><td>E</td><td>O-RING</td><td>EPDM</td><td>SPECIFY COLOR</td><td>3</td></tr><tr><td>F</td><td>SHIELD</td><td>BRASS</td><td>NICKL PLATED</td><td>1</td></tr><tr><td>G</td><td></td><td></td><td></td><td></td></tr></table>			PARTS	MATERIALS	TREATMENT	AMOUNT	A	HOUSING	PA66+GF	SPECIFY COLOR	1+1	B	CONTACT	BRASS	GOLD PLATED	2~8	C	OUTER CONTACT	BRASS	NICKL PLATED	1	D	NUT	BRASS	NICKL PLATED	3	E	O-RING	EPDM	SPECIFY COLOR	3	F	SHIELD	BRASS	NICKL PLATED	1	G				
	PARTS	MATERIALS	TREATMENT	AMOUNT																																												
A	HOUSING	PA66+GF	SPECIFY COLOR	1+1																																												
B	CONTACT	BRASS	GOLD PLATED	2~8																																												
C	OUTER CONTACT	BRASS	NICKL PLATED	1																																												
D	NUT	BRASS	NICKL PLATED	3																																												
E	O-RING	EPDM	SPECIFY COLOR	3																																												
F	SHIELD	BRASS	NICKL PLATED	1																																												
G																																																
G					<table><tr><td>Engagement force</td><td>≤50N</td><td>Rated voltage</td><td>2-5pin:60V 6-8pin:30V</td></tr><tr><td>Disengagement force</td><td>≥5N</td><td>Rated current</td><td>2-5pin:4A 6-8pin:2A</td></tr><tr><td>Mechanical lifespan</td><td>≥500</td><td>Insulation resistance</td><td>≥1000M Ω</td></tr><tr><td>IP rating</td><td>IP67</td><td>Contact resistance</td><td>≤10m Ω</td></tr><tr><td>Flammability</td><td>UL94 V-0</td><td>Operation Temperature</td><td>-40° C~105° C</td></tr></table>		Engagement force	≤50N	Rated voltage	2-5pin:60V 6-8pin:30V	Disengagement force	≥5N	Rated current	2-5pin:4A 6-8pin:2A	Mechanical lifespan	≥500	Insulation resistance	≥1000M Ω	IP rating	IP67	Contact resistance	≤10m Ω	Flammability	UL94 V-0	Operation Temperature	-40° C~105° C																						
Engagement force	≤50N	Rated voltage	2-5pin:60V 6-8pin:30V																																													
Disengagement force	≥5N	Rated current	2-5pin:4A 6-8pin:2A																																													
Mechanical lifespan	≥500	Insulation resistance	≥1000M Ω																																													
IP rating	IP67	Contact resistance	≤10m Ω																																													
Flammability	UL94 V-0	Operation Temperature	-40° C~105° C																																													
H	REV. A0	REVISION RECORD NEW RELEASE	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO: M12XXX-02-013	DWG.NO: ENDE05	 万连科技 WanLian Technology Co., Ltd																																				
					LINEAR	ANGLES	APPROVED																																									
					0.0±0.35	X°REF±6°	DESIGNER																																									
					UNIT:mm	0.00±0.25	X°±3°	DRAWN																																								
				SIZE: A4	0.000±0.10	X°X' ±2°			TITLE: M12组装式金属款屏蔽系列 母弯头 ABD编码 螺钉压接				REV: A0	SHEET: 1/1																																		
	1	2	3	4	5	6	7	8																																								