








RoHS



组合图



Recommended Panel Cut-out



P/N	TITLE
M12A02-03-301-M16	M12防水 A-CODE 2P线端公头 后锁面板式 PG9/M16 SW18T
M12A03-03-301-M16	M12防水 A-CODE 3P线端公头 后锁面板式 PG9/M16 SW18T
M12A04-03-301-M16	M12防水 A-CODE 4P线端公头 后锁面板式 PG9/M16 SW18T
M12A05-03-301-M16	M12防水 A-CODE 5P线端公头 后锁面板式 PG9/M16 SW18T
M12A06-03-301-M16	M12防水 A-CODE 6P线端公头 后锁面板式 PG9/M16 SW18T
M12A07-03-301-M16	M12防水 A-CODE 7P线端公头 后锁面板式 PG9/M16 SW18T
M12A08-03-301-M16	M12防水 A-CODE 8P线端公头 后锁面板式 PG9/M16 SW18T
M12B02-03-301-M16	M12防水 B-CODE 2P线端公头 后锁面板式 PG9/M16 SW18T
M12B03-03-301-M16	M12防水 B-CODE 3P线端公头 后锁面板式 PG9/M16 SW18T
M12B04-03-301-M16	M12防水 B-CODE 4P线端公头 后锁面板式 PG9/M16 SW18T
M12B05-03-301-M16	M12防水 B-CODE 5P线端公头 后锁面板式 PG9/M16 SW18T
M12D02-03-301-M16	M12防水 D-CODE 2P线端公头 后锁面板式 PG9/M16 SW18T
M12D03-03-301-M16	M12防水 D-CODE 3P线端公头 后锁面板式 PG9/M16 SW18T
M12D04-03-301-M16	M12防水 D-CODE 4P线端公头 后锁面板式 PG9/M16 SW18T

Engagemenr firce	≤50N	Rated voltage	2-5pin:60v 6-8PIN:30V	PARTS	MARERIALS	TREATMENT	AMOUNT					
Disengagement force	≥5N	Rated current	2-5pin:4A 6-8PIN:2A					A	HOUSING	PA66+GF	SPECIFY COLOR	1
Mechanical lifespan	≥500	Insulation resirance	≥1000MΩ					B	CONTACT	BRASS	GOLD PLATED	2~8
IP rating	IP67	Conract resistangce	≤10MΩ					C	OUTER CONTACT	BRASS	NICKL PLATED	1
Flammability	UL94 V-0	Operation Temperature	-40° C~105° C					D	NUT	BRASS	NICKL PLATED	1
				E	O-RING	EPDM	BLACK	1				

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES		SCALE	NAME	DATE	PART NO.	DWG NO.	 TERMINAL&CONNECTORS			
A0	NEW RELEASE			LINEAR	ANGLES	APPROVED		M12XXX-03-301-M16	ENDE05				
		0.0±0.25		X° REF±6°	DESIGNER								
		0.00±0.15		X° ±3°									
		0.000±0.08		X° X' ±2°	DRAWN								
TITLE								M12防水 线端公头 后锁面板式 PG9/M16 SW18T					
REV	A0	SHEET	1/1										