

	1	2	3	4	5	6	7	8																														
	The product using material and processing must conform to the "WL-PZ-001"HSF technical standard control requirements							RoHS																														
A	PIN位 X 值	2pin 1.00	3pin 1.00	4pin 1.00	5pin 1.00	6pin 0.80	7pin 0.80	8pin 0.80																														
	A-CODE 图形																																					
B	B-CODE 图形																																					
	D-CODE 图形																																					
C																																						
D																																						
	组合图																																					
E	P/N	TITLE						Recommended Panel Cut-out																														
	M12A02-03-301-M16	M12防水 A-CODE 2P线端公头 后锁面板式 PG9/M16 SW18T																																				
	M12A03-03-301-M16	M12防水 A-CODE 3P线端公头 后锁面板式 PG9/M16 SW18T																																				
	M12A04-03-301-M16	M12防水 A-CODE 4P线端公头 后锁面板式 PG9/M16 SW18T																																				
	M12A05-03-301-M16	M12防水 A-CODE 5P线端公头 后锁面板式 PG9/M16 SW18T																																				
	M12A06-03-301-M16	M12防水 A-CODE 6P线端公头 后锁面板式 PG9/M16 SW18T																																				
	M12A07-03-301-M16	M12防水 A-CODE 7P线端公头 后锁面板式 PG9/M16 SW18T																																				
	M12A08-03-301-M16	M12防水 A-CODE 8P线端公头 后锁面板式 PG9/M16 SW18T																																				
F	M12B02-03-301-M16	M12防水 B-CODE 2P线端公头 后锁面板式 PG9/M16 SW18T						<table><tr><td></td><td>PARTS</td><td>MARERIALS</td><td>TREATMENT</td><td>AMOUNT</td></tr><tr><td>A</td><td>HOUSING</td><td>PA66+GF</td><td>SPECIFY COLOR</td><td>1</td></tr><tr><td>B</td><td>CONTACT</td><td>BRASS</td><td>GOLD PLATED</td><td>2~8</td></tr><tr><td>C</td><td>OUTER CONTACT</td><td>BRASS</td><td>NICKL PLATED</td><td>1</td></tr><tr><td>D</td><td>NUT</td><td>BRASS</td><td>NICKL PLATED</td><td>1</td></tr><tr><td>E</td><td>O-RING</td><td>EPDM</td><td>BLACK</td><td>1</td></tr></table>		PARTS	MARERIALS	TREATMENT	AMOUNT	A	HOUSING	PA66+GF	SPECIFY COLOR	1	B	CONTACT	BRASS	GOLD PLATED	2~8	C	OUTER CONTACT	BRASS	NICKL PLATED	1	D	NUT	BRASS	NICKL PLATED	1	E	O-RING	EPDM	BLACK	1
	PARTS	MARERIALS	TREATMENT	AMOUNT																																		
A	HOUSING	PA66+GF	SPECIFY COLOR	1																																		
B	CONTACT	BRASS	GOLD PLATED	2~8																																		
C	OUTER CONTACT	BRASS	NICKL PLATED	1																																		
D	NUT	BRASS	NICKL PLATED	1																																		
E	O-RING	EPDM	BLACK	1																																		
	M12B03-03-301-M16	M12防水 B-CODE 3P线端公头 后锁面板式 PG9/M16 SW18T																																				
	M12B04-03-301-M16	M12防水 B-CODE 4P线端公头 后锁面板式 PG9/M16 SW18T																																				
	M12B05-03-301-M16	M12防水 B-CODE 5P线端公头 后锁面板式 PG9/M16 SW18T																																				
G	M12D02-03-301-M16	M12防水 D-CODE 2P线端公头 后锁面板式 PG9/M16 SW18T						<table><tr><td>Engagemnr firce</td><td>≤50N</td><td>Rated volage</td><td>2-5pin:60v 6-8PIN:30V</td><td></td></tr><tr><td>Disengagement force</td><td>≥5N</td><td>Rated current</td><td>2-5pin:4A 6-8PIN:2A</td><td></td></tr><tr><td>Mechanical lifespan</td><td>≥500</td><td>Insulation resisrance</td><td>≥1000MΩ</td><td></td></tr><tr><td>IP rating</td><td>IP67/IP68</td><td>Conract resistangce</td><td>≤10MΩ</td><td></td></tr><tr><td>Flammability</td><td>UL94 V-0</td><td>Operation Temperature</td><td>-40° C~105° C</td><td></td></tr></table>	Engagemnr firce	≤50N	Rated volage	2-5pin:60v 6-8PIN:30V		Disengagement force	≥5N	Rated current	2-5pin:4A 6-8PIN:2A		Mechanical lifespan	≥500	Insulation resisrance	≥1000MΩ		IP rating	IP67/IP68	Conract resistangce	≤10MΩ		Flammability	UL94 V-0	Operation Temperature	-40° C~105° C						
Engagemnr firce	≤50N	Rated volage	2-5pin:60v 6-8PIN:30V																																			
Disengagement force	≥5N	Rated current	2-5pin:4A 6-8PIN:2A																																			
Mechanical lifespan	≥500	Insulation resisrance	≥1000MΩ																																			
IP rating	IP67/IP68	Conract resistangce	≤10MΩ																																			
Flammability	UL94 V-0	Operation Temperature	-40° C~105° C																																			
	M12D03-03-301-M16	M12防水 D-CODE 3P线端公头 后锁面板式 PG9/M16 SW18T																																				
	M12D04-03-301-M16	M12防水 D-CODE 4P线端公头 后锁面板式 PG9/M16 SW18T																																				
H	REV.	REVISION RECORD		DATE	GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO:	DWG.NO:	 WanLian Technology Co., Ltd																										
	AO	NEW RELEASE			LINEAR	ANGLES				M12XXX-03-301-M16	ENDE05																											
					0.0±0.35	X'REF±6°	APPROVED																															
					0.00±0.25	X'±3'	DESIGNER			TITLE:																												
				UNIT:mm	0.000±0.10	X'X' ±2'	DRAWN			M12防水 线端公头 后锁面板式 PG9/M16 SW18T		REV: AO	SHEET: 1/1																									
	1	2	3	4	5	6	7	8																														