The product using material and processing must conform to the "WL-PZ-001"HSF technical standard control requirements

RoHS

Pin位	2Pin	3Pin4改3	4Pin	5Pin正方形	6Pin	7Pin	8Pin
A-CODE 图形							
B-CODE 图形							
D-CODE 图形							









组合图





P/N	TITLE
M12A02-08-067	M12防水 A-CODE 2P线端母头 屏蔽款+10L直纹螺母
M12A03-08-067	M12防水 A-CODE 3P线端母头 屏蔽款+10L直纹螺母
M12A04-08-067	M12防水 A-CODE 4P线端母头 屏蔽款+10L直纹螺母
M12A05-08-067	M12防水 A-CODE 5P线端母头 屏蔽款+10L直纹螺母
M12A06-08-067	M12防水 A-CODE 6P线端母头 屏蔽款+10L直纹螺母
M12A07-08-067	M12防水 A-CODE 7P线端母头 屏蔽款+10L直纹螺母
M12A08-08-067	M12防水 A-CODE 8P线端母头 屏蔽款+10L直纹螺母
M12B02-08-067	M12防水 B-CODE 2P线端母头 屏蔽款+10L直纹螺母
M12B03-08-067	M12防水 B-CODE 3P线端母头 屏蔽款+10L直纹螺母
M12B04-08-067	M12防水 B-CODE 4P线端母头 屏蔽款+10L直纹螺母
M12B05-08-067	M12防水 B-CODE 5P线端母头 屏蔽款+10L直纹螺母
M12D02-08-067	M12防水 D-CODE 2P线端母头 屏蔽款+10L直纹螺母
M12D03-08-067	M12防水 D-CODE 3P线端母头 屏蔽款+10L直纹螺母
M12D04-08-067	M12防水 D-CODE 4P线端母头 屏蔽款+10L直纹螺母

Engagemenr firce	≤50N	Rated volage	2-5Pin: 60v 6-8Pin: 30v
Disengagement force	/ 5N	Rated current	2-5Pin: 4A 6-8Pin: 2A
Mechanical lifespan	/ 500	Insulation resisrance	/ 1000MΩ
IP rating	IP67/IP68	Conract resistangce	≤10MΩ
Flammability	UL94 V-0	Operation Temperature	-40°C ~105°C

	PARTS	MARERIALS	TREATMENT	AMOUNT
A	HOUSING	PA66+GF	SPECIFY COLOR	1
B	CONTACT	BRASS	GOLD PLATED	2~8
C	OUTER CONTACT	BRASS	NICKL PLATED	1
D	NUT	BRASS	NICKL PLATED	1
E	O-RING	EPDM	BLACK	1

REV.	REVISION RECORD	DATE
A0	NEW RELEASE	21.11.17

GENERAL TOLERANCES

LINEAR	ANGLES
0.0±0.35	X°REF±6°
0.00±0.25	X°±3°
0.000±0.10	X°X' ±2°

UNIT: mm

SIZE: A4

SCALE: 1:1

	NAME	DATE
APPROVED		
DESIGNER		
DRAWN		

PART.NO: M12XXX-08-067

DWG.NO: ENDE05

TITLE: M12防水 2-8P线端母头 屏蔽款+10L直纹螺母

万连科技 WanLian Technology Co., Ltd

REV: A0 SHEET: 1/1