





The product using material and processing must conform to the "WI-PZ-001"HSF technical standard control requirements

ROHS

空第17P



NOTE:
 1.MATERIAL SPECIFICATION:
 1-1.HOUSING: PA6T,UL94V-0
 1-2.CONTACTS: BRASS
 2.PLATING SPECIFICATION:
 2-1.CONTACTS:
 GOLD FLASH OVER NICKEL
 3.ELECTRICAL PERFORMANCE:
 3-1.CURRENT RATING: 2A
 3-2.CONTACT RESISTANCE: 30 mΩ MAX
 3-3.INSULATION RESISTANCE: 1000MΩ Min
 3-4.DIELECTRIC WITHSTANDING : 300V
 4.ENVIRONMENTAL PERFORMANCE:
 4-1.OPERATING TEMPERATURE: -40°C~+105°C.
 5.PACKAGE SPEC: TRAY
 6.P/N:
 PH2005 20 M 9-2 XX 1 X X X 03
 SERIES NO: _____ HOUSING: 1-PA6T
 HEIGHT: _____ COLOR: A-BLACK
 20: 2.0mm MALE FEMALE: _____ PLATING: A-ALL AU G/F
 M-MALE C-BRIGHT TIN
 ANGLE: _____ 9-90°
 ROW NO: _____ 2-DOUBLE ROW
 PIN Q' PY: _____ TERMPOINT: 1-DIP
 02~80



RECOMMENDED P.C.B LAYOUT
 P.C.B TOLERANCE:±0.05

REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO: PH200520M9-2XX1XXX03	DWG.NO: ENDE05	 WanLian Technology Co., Ltd	
A0	NEW RELEASE	21.10.15		LINEAR	ANGLES	APPROVED	Wang_jr	21.10.15				
			UNIT:mm	0.00±0.25	X'±3'	DESIGNER	Gao_Han	21.10.15	TITLE: 2.0双排针H2.0W4.0 90° 双排 2X16P排针弯凹槽 PC2.8 空第17P	REV: A0		SHEET: 1/1
			SIZE: A4	0.000±0.10	X'X' ±2'	DRAWN	Gao_Han	21.10.15				