




The product using material and processing must conform to the "WI-PZ-001"HSF technical standard control requirements



NOTE:
1.MATERIAL SPECIFICATION:
1-1.HOUSING: PA6T,UL94V-0
1-2.CONTACTS: BRASS
2.PLATING SPECIFICATION:
2-1.CONTACTS:
GOLD FLASH OVER NICKEL
3.ELECTRICAL PERFORMANCE:
3-1.CURRENT RATING: 3A
3-2.CONTACT RESISTANCE: 30 mΩ MAX
3-3.INSULATION RESISTANCE: 1000MΩ Min
3-4.DIELECTRIC WITHSTANDING : 500V
4.ENVIRONMENTAL PERFORMANCE:
4-1.OPERATING TEMPERATURE: -40°C~+105°C.
5.PACKAGE SPEC: PE BAG
6.P/N:

PH2541 25 M 0-1 XX 1 X X X 08
SERIES NO: _____
HEIGHT: _____
25: 2.5mm
MALE FEMALE: _____
M-MALE
ANGLE: _____
0-180°
ROW NO: _____
1-SINGLE ROW
PIN Q'PY: _____
01~40
HOUSING:
1-PA6T
2-LCP
3-PBT
COLOR:
A-BLACK
PLATING:
A-ALL AU G/F
TERMIPOINT:
1-DIP

RECOMMENDED P. C. B LAYOUT
P. C. B TOLERANCE: ±0.05

REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO: PH254125M0-1XX1XXX08	DWG.NO: ENDE05	 WanLian Technology Co., Ltd	
A0	NEW RELEASE	21.10.15		LINEAR	ANGLES	APPROVED	Wang_jr	21.10.15				
				0.0±0.35	X'REF±6°							
				UNIT:mm	0.00±0.25	X'±3°	DESIGNER	Gao_Han	21.10.15	TITLE: Pitch 2.54mm 180° 单排 DIP 单塑排针 L=9.5MM PC3.0		
			SIZE: A4	0.000±0.10	X'X' ±2°	DRAWN	Gao_Han	21.10.15	REV: A0			SHEET: 1/1