

The product using material and processing must conform to the "WI-PZ-001"HSF technical standard control requirements

RoHS+HF

12.50±0.2

10.1±0.1

27.80±0.2

25.27±0.1

34.40±0.2

15.60±0.1

7.70±0.1

14.70±0.2

17.15±0.1

NOTE:

1.MATERIAL SPECIFICATION:
1-1.HOUSING:PA66,UL94V-0

2.MECHANICAL PERFORMANCE:
2-1.INSERTION FORCE: 1KGF/PIN MAX
2-2.REMOVAL FORCE: 3KGF/PIN MIN
2-3.DURABILITY: 25 CYCLES.

3.ELECTRICAL PERFORMANCE:
3-1. RATED CURRENT : 10A
RATED VOLTAGE : 250V
3-2.INSULATION RESISTANCE: 1000MΩ MIN
CONTACT RESISTANCE : 30mΩ MAX
3-3.WITHSTANDING VOLTAGE:1500V AC

4.ENVIRONMENTAL PERFORMANCE:
OPERATING TEMPERATURE: -40°C~+90°C.

5.PACKAGE SPEC:PE BAG

6.P/N:

A2201 H F-2 20 X 0

SERIES NO:

CONNECTOR:
H-HOUSING

MALE FEMALE:
F-FEMALE

COLOR:
A-BLACK
K-WHITE
S-NATURE

PIN Q'PY:
02~40

ROW NO:
2-DOUBLE ROW

3.07

2.60

9-2.27

2.60

2.98

REV.

REVISION RECORD

DATE

⊕

≡

UNIT:mm

SIZE: A4

GENERAL TOLERANCES

LINEAR

0.0±0.35

0.00±0.25

0.000±0.10

ANGLES

X°REF±6°

X°±3°

X°X' ±2°

SCALE:
1:1

APPROVED

DESIGNER

DRAWN

NAME

Han_Gao

Zijun_Huang

DATE

21.01.13

21.01.13

21.01.13

PART.NO:

A2201HF-220X0

TITLE:

PITCH 2.20mm 母胶壳

DWG.NO:

ENDE05

万连科技

WanLian Teconology Co., Ltd

REV: A0

SHEET: 1/1

12345678