

The product using material and processing must conform to the "WI-PZ-001"HSF technical standard control requirements

RoHS+HF

29.40±0.2

26.20±0.2

19.30±0.2

13.70±0.2

8.00±0.2

33.60±0.3

32.80±0.3

15.50±0.2

36.00±0.3

13x2.20

13.30±0.2

3.00

7.60±0.2

32.80±0.3

15.50±0.2

13.30±0.2

NOTE:

1.MATERIAL SPECIFICATION:
1-1.HOUSING:PA66,UL94V-0

2.MECHANICAL PERFORMANCE:
2-1.INSERTION FORCE: 1KGF/PIN MAX
2-2.REMOVAL FORCE: 3KGF/PIN MIN
2-3.DURABILITY: 25 CYCLES.

3.ELECTRICAL PERFORMANCE:
3-1. RATED CURRENT : 10A
RATED VOLTAGE : 250V
3-2.INSULATION RESISTANCE: 1000MΩ MIN
CONTACT RESISTANCE : 30mΩ MAX
3-3.WITHSTANDING VOLTAGE:1500V AC

4.ENVIRONMENTAL PERFORMANCE:
OPERATING TEMPERATURE: -40°C~+90°C.

5.PACKAGE SPEC:PE BAG

6.P/N:

A2201 H F-2 28 X 0

SERIES NO:

CONNECTOR:
H-HOUSING

MALE FEMALE:
F-FEMALE

COLOR:
A-BLACK
K-WHITE
S-NATURE

PIN Q'PY:
02~40

ROW NO:
2-DOUBLE ROW

REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO:	DWG.NO:	 WanLian Teconology Co., Ltd			
A0	NEW RELEASE	21.01.13		LINEAR	ANGLES	APPROVED	Wang_jr	21.01.13	A2201HF-228X0					
				0.0±0.35	X°REF±6°	DESIGNER	Han_Gao	21.01.13	TITLE: PITCH 2.20mm 母胶壳					
				0.00±0.25	X°±3°	DRAWN	Zijun_Huang	21.01.13						
			UNIT:mm	0.00±0.10	X°X' ±2°						REV: A0	SHEET: 1/1		
			SIZE: A4											
1	2	3	4	5	6	7	8							