

1	2	3	4	5	6	7	8																																																																		
The product using material and processing must conform to the "WI-PZ-001"HSF technical standard control requirements																																																																									
					RoHS NOTE: 1.MATERIAL SPECIFICATION: 1-1.HOUSING: PA6T,UL94V-0 1-2.CONTACTS: BRASS 2.PLATING SPECIFICATION: 2-1.CONTACTS: TIN/GOLD FLASH PLATED OVER ALL. 3.ELECTRICAL PERFORMANCE: 3-1.CURRENT RATING: 2A 3-2.CONTACT RESISTANCE: 30 mΩ MAX 3-3.INSULATION RESISTANCE: 1000MΩ Min 3-4.DIELECTRIC WITHSTANDING : 500V 4.ENVIRONMENTAL PERFORMANCE: 4-1.OPERATING TEMPERATURE: -40°C~+105°C. 5.PACKAGE SPEC: TRAY 6.P/N:																																																																				
					EJ20751 SERIES NO: MALE FEMALE: ANGLE: ROW NO: PIN Q'PY: F 0-2 XX 2 X X X TYPE: 1-LONG LATCH 2-SHORT LATCH COLOR: A-BLACK PLATING: A-ALL AU G/F TERMIPOINT: 2-SMT																																																																				
			<table><tr><th>TYPE</th><th>L</th></tr><tr><td>1-LONG LATCH</td><td>20.80</td></tr><tr><td>2-SHORT LATCH</td><td>17.00</td></tr></table>		TYPE	L	1-LONG LATCH	20.80	2-SHORT LATCH	17.00	<table><tr><th>Circuit</th><th colspan="2">Dimensions(mm)</th><th>Circuit</th><th colspan="2">Dimensions(mm)</th></tr><tr><td></td><th>A</th><th>B</th><td></td><th>A</th><th>B</th></tr><tr><td>06</td><td>4.00</td><td>21.60</td><td>26</td><td>24.00</td><td>41.60</td></tr><tr><td>08</td><td>6.00</td><td>23.60</td><td>30</td><td>28.00</td><td>45.60</td></tr><tr><td>10</td><td>8.00</td><td>25.60</td><td>34</td><td>32.00</td><td>49.60</td></tr><tr><td>12</td><td>10.00</td><td>27.60</td><td>40</td><td>38.00</td><td>55.60</td></tr><tr><td>14</td><td>12.00</td><td>29.60</td><td>44</td><td>42.00</td><td>59.60</td></tr><tr><td>16</td><td>14.00</td><td>31.60</td><td>50</td><td>48.00</td><td>65.60</td></tr><tr><td>20</td><td>18.00</td><td>35.60</td><td>60</td><td>58.00</td><td>75.60</td></tr><tr><td>24</td><td>22.00</td><td>39.60</td><td></td><td></td><td></td></tr></table>			Circuit	Dimensions(mm)		Circuit	Dimensions(mm)			A	B		A	B	06	4.00	21.60	26	24.00	41.60	08	6.00	23.60	30	28.00	45.60	10	8.00	25.60	34	32.00	49.60	12	10.00	27.60	40	38.00	55.60	14	12.00	29.60	44	42.00	59.60	16	14.00	31.60	50	48.00	65.60	20	18.00	35.60	60	58.00	75.60	24	22.00	39.60			
TYPE	L																																																																								
1-LONG LATCH	20.80																																																																								
2-SHORT LATCH	17.00																																																																								
Circuit	Dimensions(mm)		Circuit	Dimensions(mm)																																																																					
	A	B		A	B																																																																				
06	4.00	21.60	26	24.00	41.60																																																																				
08	6.00	23.60	30	28.00	45.60																																																																				
10	8.00	25.60	34	32.00	49.60																																																																				
12	10.00	27.60	40	38.00	55.60																																																																				
14	12.00	29.60	44	42.00	59.60																																																																				
16	14.00	31.60	50	48.00	65.60																																																																				
20	18.00	35.60	60	58.00	75.60																																																																				
24	22.00	39.60																																																																							
<table><tr><td>REV.</td><td>REVISION RECORD</td><td>DATE</td><td rowspan="4"></td><td colspan="2">GENERAL TOLERANCES</td><td>SCALE: 1:1</td><td>NAME</td><td>DATE</td><td>PART.NO:</td><td>DWG.NO:</td><td rowspan="4"></td></tr><tr><td>AO</td><td>NEW RELEASE</td><td>22.03.19</td><td>LINEAR</td><td>ANGLES</td><td>APPROVED</td><td>Wang_jr</td><td>22.03.19</td><td>EJ20751F0-2XX2XXX</td><td>ENDE05</td></tr><tr><td></td><td></td><td></td><td>0.0±0.35</td><td>X'REF±6°</td><td>CHECK</td><td>XueZe_Ma</td><td>22.03.19</td><td>TITLE:</td><td></td></tr><tr><td></td><td></td><td></td><td>UNIT:mm</td><td>0.00±0.25</td><td>X'±3°</td><td></td><td></td><td>Pitch 2.0mm 180° 双排 SMT 牛角</td><td></td></tr><tr><td></td><td></td><td></td><td>SIZE: A4</td><td>0.000±0.10</td><td>X'X' ±2°</td><td>DRAWN</td><td>LanXuan_Hou</td><td>22.03.19</td><td></td><td></td><td>REV: A0</td><td>SHEET: 1/1</td></tr></table>			REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO:	DWG.NO:		AO	NEW RELEASE	22.03.19	LINEAR	ANGLES	APPROVED	Wang_jr	22.03.19	EJ20751F0-2XX2XXX	ENDE05				0.0±0.35	X'REF±6°	CHECK	XueZe_Ma	22.03.19	TITLE:					UNIT:mm	0.00±0.25	X'±3°			Pitch 2.0mm 180° 双排 SMT 牛角					SIZE: A4	0.000±0.10	X'X' ±2°	DRAWN	LanXuan_Hou	22.03.19			REV: A0	SHEET: 1/1																
REV.	REVISION RECORD	DATE		GENERAL TOLERANCES			SCALE: 1:1	NAME	DATE	PART.NO:	DWG.NO:																																																														
AO	NEW RELEASE	22.03.19		LINEAR	ANGLES		APPROVED	Wang_jr	22.03.19	EJ20751F0-2XX2XXX	ENDE05																																																														
				0.0±0.35	X'REF±6°		CHECK	XueZe_Ma	22.03.19	TITLE:																																																															
				UNIT:mm	0.00±0.25	X'±3°			Pitch 2.0mm 180° 双排 SMT 牛角																																																																
			SIZE: A4	0.000±0.10	X'X' ±2°	DRAWN	LanXuan_Hou	22.03.19			REV: A0	SHEET: 1/1																																																													
1	2	3	4	5	6	7	8																																																																		