



Note: 11257TOP-XX-XX
 符号 Mark
 NK : NO Mark

- Finish
- 0A--Gold-flash
 - 0B--2u"
 - 0C--3u"
 - 0D--4u"
 - 0E--5u"
 - 0F--10u"
 - 0G--15u"
 - 0H--30u"
 - 0I--50u"
 - 2E--Tin-plated
 - 3E--Matte Tin-plated
 - 5A--Gold-flash
 - 5B--2u"
 - 5C--3u"
 - 5D--4u"
 - 5E--5u"

Part No	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
11257TOP-0X-XX	AWG#26~#32	0.90mm(max)	Phosphor Bronze	Gold-plated contact area	20,000 pcs
11257TOP-2E-XX	AWG#26~#32	0.90mm(max)	Phosphor Bronze	Tin-plated	20,000 pcs
11257TOP-3E-XX	AWG#26~#32	0.90mm(max)	Phosphor Bronze	Matte Tin-plated	20,000 pcs
11257TOP-5X-XX	AWG#26~#32	0.90mm(max)	Phosphor Bronze	Gold Plated on Overall.	20,000 pcs

The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES	SCALE	NAME	DATE	PART NO.	DWG NO.
C4	新增电镀规格	15.02.02	LINEAR 0.0±0.25 ANGLES X° REF±6°	1:1	[Signature]	23.11.28	11257TOP-XX-XX	ENDE05
C5	新增电镀规格	16.06.16						
C6	变更公司名称	17.01.12	UNIT: MM 0.00±0.15 SIZE: A4 0.00±0.08		Designer [Signature]	23.11.28	TITLE GHR 1.25mm PITCH Terminal	
D0	ECN2023117732 Update drawing	23.11.28	X° X' ±2°		Drawn WN	23.11.28		

