



Specifications:  
 Rated Voltage : 100V AC/DC  
 Rated Current : 3A AC,DC(AWG# 22)  
 Withstand Voltage : 800V AC Min.  
 After environmental test 500V AC Min  
 Insulation Resistance : 1000MΩ Min.  
 After environmental test 500MΩ Min.  
 Contact Resistance : 15mΩ Max  
 After environmental test : 25mΩ Max  
 Temperature Range : -25°C~+85°C  
 Including temperature rise in applying electrical current  
 The product using material and processing  
 must conform to the "WI-PZ-142"HSF  
 technical standard control requirements

12002 H00- NPX-L-A-HF  
 HF: Halogen Free  
 Type A  
 Lock  
 Color A=Black  
 No code=White  
 No. of Circuits  
 H00 : Up Contact



Dimensional Ordering Information:

Circuits	Dimensions	
	A	B
2P	2.0	5.4
3P	4.0	7.4
4P	6.0	9.4
5P	8.0	11.4
6P	10.0	14.0
7P	12.0	16.0
8P	14.0	18.0
9P	16.0	20.0
10P	18.0	22.0
15P	28.0	32.0

Part No.	Material	Color
12002H00-NP-L-A-HF	Nylon 66,UL94-V0	White

REV.	REVISION RECORD	DATE	UNIT: MM	GENERAL TOLERANCES		SCALE 1:1	NAME	DATE
				LINEAR	ANGLES			
X0	The new version file were released	2022.04.22		0.0±0.25	X° REF±6°		Nelson	22.04.22
				0.00±0.15	X° ±3°		WU	22.04.22
			SIZE: A4	0.000±0.08	X° X' ±2°		YZY	2022.04.22

PART NO.	DWG NO.
12002H00-NP-L-A-HF	ENDE05
TITLE	
PA 2.0 Housing	

<b>JCTC</b> ®			
TERMINAL&CONNECTORS			
REV	X0	SHEET	1/1