



12002W00-NP-L-HF
① ② ③ ④ ⑤

- ① Series No.
- ② W90 : Side Contact
W00 : Up Contact
- ③ No. of Circuits
- ④ L : With Lock
- ⑤ HF : Halogen Free

Specifications:
 Rated Voltage : 250V AC/DC
 Rated Current : 3A AC,DC
 Withstand Voltage : 800V AC/minute
 Contact Resistance : 10mΩ(MAX.)
 Insulation Resistance : 1000MΩ(MIN.)
 Temperature Range : -25°C~+85°C
 The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

Part No.	Insulator	Color	Contact
12002W00-NP-L-HF	Nylon 66+15%GF,UL94V-0	Natural(White)	Brass/Tin-plated
12002W00-NPA-L-HF	Nylon 66+15%GF,UL94V-0	Black	Brass/Tin-plated
12002W00-NPC-L-HF	Nylon 66+15%GF,UL94V-0	Red	Brass/Tin-plated

PART NO.	Dimensions	
	A	B
2P	--	6.00
3P	4.00	8.00
4P	6.00	10.00
5P	8.00	12.00
6P	10.00	14.00
7P	12.00	16.00
8P	14.00	18.00
9P	16.00	20.00
10P	18.00	22.00
11P	20.00	24.00
12P	22.00	26.00
13P	24.00	28.00
14P	26.00	30.00
15P	28.00	32.00
16P	30.00	34.00

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES		SCALE 1:1	NAME	DATE	PART NO.	DWG NO.
			LINEAR	ANGLES					
AO	新图面发行	2017.05.12	 UNIT: MM SIZE: A4	0.0±0.25	X° REF±6°	APPROVED	21.10.20	12002W00-NP-L-HF	ENDE05
A1	依YB2110090003新增规格	2021.10.20		0.00±0.15	X° ±3°	DESIGNER	21.10.20		
				0.000±0.08	X° X'±2°	DRAWN	2021.10.20		



REV	A1	SHEET	1/1
-----	----	-------	-----