

RoHS

Specifications:

Rated Voltage : 250V AC/DC

Rated Current : 3A AC,DC

Withstand Voltage : 800V AC/minute

Contact Resistance : 10mΩ(MAX.)

Insulation Resistance : 1000MΩ(MIN.)

Temperature Range : -25°C~+85°C

12002W90-2XNP-H1-HF

① ② ③ ④ ⑤

① Series No.

② W90 : Side Contact

W00 : Up Contact

③ No. of Circuits

④ H1 : High temperature plastic

⑤ HF : Halogen Free

2.00±0.10 10.00 SQ 0.50±0.03

2.00±0.10

2.000

2.000

φ0.70<sup>+0.10</sup><sub>-0.00</sub>

P.C.B LAYOUT

14.0

5.05±0.25

9.50±0.25

6.50±0.25

2.00±0.20

3.00±0.20



Part No.	Material	Color	PIN Material
12002W90-2X6P-H1-HF	LCP,UL94V-0	本色	Brass/Tin-plated

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES	SCALE:	NAME	DATE	<b>JCTC®</b> 胜蓝科技股份有限公司 TERMINAL&CONNECTORS 东莞市富智达电子科技有限公司	PART NO:
AO	新图面发行	15.07.29	LINEAR	1:1	李智勇	17.06.02		12002W90-2X6P-H1-HF ENDE05
A1	更新公司名称	17.06.02	ANGLES	APPROVED	李智勇	17.06.02		
			0.0±0.25 X° REF±6°	DESIGNER	伍文聪	17.06.02		
			UNIT: MM 0.00±0.15 X° ±3°	DRAWN	伍文聪	17.06.02	TITLE: PHD双排 2.00mm PITCH WAFER	DWG. NO:
			SIZE: A4 0.000±0.08 X° X'±2°					REV: A1 SHEET: 1/1