



PART NO.	Dimensions	
	A	B
2P	--	6.00
3P	4.00	8.00
4P	6.00	10.00
5P	8.00	12.00
6P	10.00	14.00
7P	12.00	16.00
8P	14.00	18.00
9P	16.00	20.00
10P	18.00	22.00
11P	20.00	24.00
12P	22.00	26.00
13P	24.00	28.00
14P	26.00	30.00
15P	28.00	32.00
16P	30.00	34.00

- 12002W90-NP-L-S6-HF  
 ① ② ③ ④ ⑤ ⑥
- ① Series No.
  - ② W90 : Side Contact  
W00 : Up Contact
  - ③ No. of Circuits
  - ④ L : With Lock
  - ⑤ S6 : S6 TYPE
  - ⑥ HF : Halogen Free

Specifications:  
 Rated Voltage : 250V AC/DC  
 Rated Current : 3A AC,DC  
 Withstand Voltage : 800V AC/minute  
 Contact Resistance : 10mΩ(MAX.)  
 Insulation Resistance : 1000MΩ(MIN.)  
 Temperature Range : -25°C~+85°C

The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

胜蓝科技股份有限公司  
 2023.01.05  
 工程部  
 技术文件发行

Part No.	Insulator	PIN Material
12002W90-NP-L-S6-HF	Nylon 66,UL94V-0/Natural(White)/植	Brass/Tin-plated

REV.	REVISION RECORD	DATE	UNIT: MM SIZE: A4	GENERAL TOLERANCES		SCALE	NAME	DATE	PART NO.	DWG NO.	 TERMINAL&CONNECTORS
A0	新图面发行	23.01.04		LINEAR	ANGLES	1:1					
			0.0±0.25	X° REF±6°	APPROVED	Nelson	23.01.06	12002W90-NPX-L-S6-HF	ENDE05		
			0.00±0.15	X° ±3°	DESIGNER	mc	23.01.04	TITLE			
			0.000±0.08	X° X' ±2°	DRAWN	ZZK	2023.01.04	PA 2.00mm PITCH DIP TYPE WAFER (外露针长2.4mm)			

REV	AO	SHEET	1/1
-----	----	-------	-----