



Specifications:  
 Rated Voltage : 250V AC/DC  
 Rated Current : 3A AC,DC  
 Withstand Voltage : 1000V AC/minute  
 Contact Resistance : 30mΩ(Max.)  
 Insulation Resistance : 1000MΩ(Min.)  
 Temperature Range : -25°C~+85°C  
 Contact: Brass/Matte Tin-plated  
 Brass/Gold-flash  
 Material: Thermal Plasticity Resin, UL94V-0  
 Halogen Free  
 Color: Natural(Beige)  
 The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

Circuits	Dimensions		
	A	B	C
2P	--	6.00	1.50
3P	4.00	8.00	1.50
4P	6.00	10.00	3.50
5P	8.00	12.00	5.50
6P	10.00	14.00	7.50
7P	12.00	16.00	9.50
8P	14.00	18.00	11.50
9P	16.00	20.00	13.50
10P	18.00	22.00	15.50
11P	20.00	24.00	
12P	22.00	26.00	
13P	24.00	28.00	
14P	26.00	30.00	
15P	28.00	32.00	
16P	30.00	34.00	

- 12005W00-NP-S1-3E-HF  
 ① ② ③ ④ ⑤ ⑥
- ① Series No.
  - ② W90 : Side Contact  
W00 : Up Contact
  - ③ No. of Circuits
  - ④ S1: S1 TYPE
  - ⑤ 3E: Matte Tin-plated  
5A: Gold-flash  
5H: Gold-plated 30u"  
5C: Gold-plated 3u"
  - ⑥ HF: Halogen Free

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES		SCALE	NAME	DATE	PART NO.	DWG NO.	 <b>JCTC</b> ® TERMINAL&CONNECTORS
C0	新图面发行	2013.08.13	LINEAR	ANGLES	1:1	APPROVED	22.12.07	12005W00-NP-S1-3E-HF	ENDE05	
C1	更新公司名称	2017.03.10			0.0±0.25					
C2	依PBJOA202207200005新增规格	2022.08.01	UNIT: MM	X° ±3°	DRAWN	Hui	2022.12.07	TITLE	2.00mm PITCH DIP TYPE 180° WAFER	
C3	依PBJOA202211250001新增规格	2022.12.07								