



镀镍&锡&金电镀测点



The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

Note: 13962T2P-XX

Finish _____
 2E—Stamping before Tin-plated
 0A—Stamping before Gold Flash

Part No.	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
13962T2P-2E	AWG #16~#20	1.70-2.80mm	Phosphor Bronze	Ni 30u"Min. Tin-plated 60u"Min.	2,500 pcs
13962T2P-0A	AWG #16~#20	1.70-2.80mm	Phosphor Bronze	Ni 30u"Min. Gold Flash	2,500 pcs

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES	SCALE:	NAME	DATE	料号 PART. NO:	文件编号 NUMBER
A0	新图面发行	16. 03. 03	LINEAR	1:1			13962T2P-XX	ENDE05
A1	TN1703070019	17. 03. 07	ANGLES					
A2	依TN1808170149设变	18. 08. 17	0.0±0.25 X° REF±6°					
A3	依YB20230625002新增电镀规格	23. 08. 14	0.00±0.15 X° ±3°					
			UNIT: MM					
			SIZE: A4					
			0.000±0.08 X° X'±2°					



REV: A3 SHEET: 1/1