

环保物料

Recommend P.C.B Layout

Specifications:
 Rated Voltage : 250V AC/DC
 Rated Current : 10A AC,DC
 Withstand Voltage : 1500V AC/minute
 Contact Resistance : 10mΩ(MAX.)
 Insulation Resistance : 1000MΩ(MIN.)
 Temperature Range : -25°C~+85°C
 Contact: Brass/Tin-plated
 Material: Nylon 66,UL94V-0 Halogen Free

Part No.	Material	Color
13962W00-4P-HF-003	Nylon66,UL94V-0 Brass/Tin plated	white

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES	SCALE:	NAME	DATE
A0	新图面发行	15.05.13	LINEAR	1:1		
			0.0±0.25	APPROVED	杨朝阳	15.05.13
			0.00±0.15	DESIGNER	杨朝阳	15.05.13
			0.000±0.08	DRAWN	杨朝阳	15.05.13

JCTC ®	□ 苏州伟聚	□ 东莞胜景	PART. NO:
TERMINAL&CONNECTORS	■ 东莞胜蓝		13962W00-4P-HF-003
TITLE:			DWG. NO:
3.96mm Pitch DIP Type 180° Wafer			ENDE05
REV:			A0
SHEET:			1/1