

1	2	3	4	5	6	7	8																																																																
The product using material and processing must conform to the "WI-PZ-001"HSF technical standard control requirements																																																																							
RoHS+HF																																																																							
			NOTE: 1.MATERIAL SPECIFICATION: 1-1.HOUSING: PA66,UL94V-0 1- 2.TERMINAL: PHOSPHOR BRONZE 2.PLATING SPECIFICATION: 2-1.TERMINAL: BRIGHT TIN PLATED OVER ALL. 3.MECHANICAL PERFORMANCE: 3-1.RETENTIVITY FORCE: 0.6KGF/Pin Min 3-2.DURABILITY: 50 CYCLES. 4.ELECTRICAL PERFORMANCE: 4-1.CURRENT RATING: 1A RATED VOLTAGE : 50V 4-2.CONTACT RESISTANCE: 20 mΩ MAX 4-3.INSULATION RESISTANCE: 500MΩ Min 4-4.DIELECTRIC WITHSTANDING : 500V AC 5.ENVIRONMENTAL PERFORMANCE: 5-1.OPERATING TEMPERATURE: -25℃~+85℃. 6.PACKAGE SPEC: PE BAG 7.P/N: A1501 H 2 M-1 XX X 0 SERIES NO: _____ CONNECTOR: _____ H-HOUSING TYPE CODE: _____ MALE FEMALE: _____ M-MALE COLOR: A-BLACK K-WHITE PIN Q'PY: 02~13 ROW NO: 1-SINGLE ROW																																																																				
			<table><tr><th>Circuit</th><th colspan="3">Dimensions(mm)</th><th>Circuit</th><th colspan="3">Dimensions(mm)</th></tr><tr><td></td><td>A</td><td>B</td><td>C</td><td></td><td>A</td><td>B</td><td>C</td></tr><tr><td>02</td><td>1.50</td><td>3.50</td><td>4.50</td><td>08</td><td>10.50</td><td>12.50</td><td>13.50</td></tr><tr><td>03</td><td>3.00</td><td>5.00</td><td>6.00</td><td>09</td><td>12.00</td><td>14.00</td><td>15.00</td></tr><tr><td>04</td><td>4.50</td><td>6.50</td><td>7.50</td><td>10</td><td>13.50</td><td>15.50</td><td>16.50</td></tr><tr><td>05</td><td>6.00</td><td>8.00</td><td>9.00</td><td>11</td><td>15.00</td><td>17.00</td><td>18.00</td></tr><tr><td>06</td><td>7.50</td><td>9.50</td><td>10.50</td><td>12</td><td>16.50</td><td>18.50</td><td>19.50</td></tr><tr><td>07</td><td>9.00</td><td>11.00</td><td>12.00</td><td>13</td><td>18.00</td><td>20.00</td><td>21.00</td></tr></table>					Circuit	Dimensions(mm)			Circuit	Dimensions(mm)				A	B	C		A	B	C	02	1.50	3.50	4.50	08	10.50	12.50	13.50	03	3.00	5.00	6.00	09	12.00	14.00	15.00	04	4.50	6.50	7.50	10	13.50	15.50	16.50	05	6.00	8.00	9.00	11	15.00	17.00	18.00	06	7.50	9.50	10.50	12	16.50	18.50	19.50	07	9.00	11.00	12.00	13	18.00	20.00	21.00
Circuit	Dimensions(mm)			Circuit	Dimensions(mm)																																																																		
	A	B	C		A	B	C																																																																
02	1.50	3.50	4.50	08	10.50	12.50	13.50																																																																
03	3.00	5.00	6.00	09	12.00	14.00	15.00																																																																
04	4.50	6.50	7.50	10	13.50	15.50	16.50																																																																
05	6.00	8.00	9.00	11	15.00	17.00	18.00																																																																
06	7.50	9.50	10.50	12	16.50	18.50	19.50																																																																
07	9.00	11.00	12.00	13	18.00	20.00	21.00																																																																
			<table><tr><td>REV.</td><td>REVISION RECORD</td><td>DATE</td><td rowspan="4"></td><td colspan="2">GENERAL TOLERANCES</td><td>SCALE: 1:1</td><td>NAME</td><td>DATE</td><td rowspan="4">PART.NO: A1501H2M-1XXX0</td><td rowspan="4">DWG.NO: ENDE05</td><td rowspan="4"></td><td rowspan="4">WanLian Technology Co., Ltd</td></tr><tr><td>A0</td><td>NEW RELEASE</td><td>22.10.28</td><td>LINEAR</td><td>ANGLES</td><td>APPROVED</td><td>Wang_jr</td><td>22.10.28</td></tr><tr><td></td><td></td><td></td><td>0.0±0.35</td><td>X°REF±6°</td><td>CHECK</td><td>XueZe_Ma</td><td>22.10.28</td></tr><tr><td></td><td></td><td></td><td>UNIT: mm</td><td>0.00±0.25</td><td>X°±3°</td><td>DRAWN</td><td>LanXuan_Hou</td><td>22.10.28</td></tr><tr><td></td><td></td><td></td><td>SIZE: A4</td><td>0.000±0.10</td><td>X°X' ±2°</td><td></td><td></td><td></td><td colspan="2">TITLE: Pitch1.50 mm ZH 刺破式单排公胶壳 AWG#32</td><td>REV: A0</td><td>SHEET: 1/1</td></tr></table>					REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO: A1501H2M-1XXX0	DWG.NO: ENDE05		WanLian Technology Co., Ltd	A0	NEW RELEASE	22.10.28	LINEAR	ANGLES	APPROVED	Wang_jr	22.10.28				0.0±0.35	X°REF±6°	CHECK	XueZe_Ma	22.10.28				UNIT: mm	0.00±0.25	X°±3°	DRAWN	LanXuan_Hou	22.10.28				SIZE: A4	0.000±0.10	X°X' ±2°				TITLE: Pitch1.50 mm ZH 刺破式单排公胶壳 AWG#32		REV: A0	SHEET: 1/1													
REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO: A1501H2M-1XXX0	DWG.NO: ENDE05			WanLian Technology Co., Ltd																																																										
A0	NEW RELEASE	22.10.28		LINEAR	ANGLES	APPROVED	Wang_jr	22.10.28																																																															
				0.0±0.35	X°REF±6°	CHECK	XueZe_Ma	22.10.28																																																															
				UNIT: mm	0.00±0.25	X°±3°	DRAWN	LanXuan_Hou			22.10.28																																																												
			SIZE: A4	0.000±0.10	X°X' ±2°				TITLE: Pitch1.50 mm ZH 刺破式单排公胶壳 AWG#32		REV: A0	SHEET: 1/1																																																											
1	2	3	4	5	6	7	8																																																																