





1	2	3	4	5	6	7	8
The product using material and processing must conform to the "WI-PZ-001"HSF technical standard control requirements			RoHS+HF				
A							A
B							B
C							C
D							D
E							E
F							F
G							G
H							H



NOTE:

1.MATERIAL SPECIFICATION:
1-1.HOUSING:PBT,UL94V-0

2.MECHANICAL PERFORMANCE:
2-1.INSERTION FORCE: 1KGF/PIN MAX
2-2.REMOVAL FORCE: 3KGF/PIN MIN
2-3.DURABILITY: 25 CYCLES.

3.ELECTRICAL PERFORMANCE:
3-1. RATED CURRENT : 10A
RATED VOLTAGE : 250V
3-2.INSULATION RESISTANCE: 1000MΩ MIN
CONTACT RESISTANCE : 30mΩ MAX
3-3.WITHSTANDING VOLTAGE:1500V AC

4.ENVIRONMENTAL PERFORMANCE:
OPERATING TEMPERATURE: -40°C~+90°C.

5.PACKAGE SPEC:PE BAG

6.P/N:

A2201 H M-2 16 X 0

SERIES NO:

CONNECTOR:
H-HOUSING

MALE FEMALE:
M-MALE

COLOR:
A-BLACK
K-WHITE
S-NATURE

PIN Q'PY:
02~40

ROW NO:
2-DOUBLE ROW

REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO: A2201HM-216X0	DWG.NO: ENDE05	 WanLian Teconology Co., Ltd			
A0	NEW RELEASE	21.01.13		LINEAR	ANGLES	APPROVED						Wang_jr	21.01.13	
				0.0±0.35	X°REF±6°	DESIGNER						Han_Gao	21.01.13	
				UNIT:mm	0.00±0.25	X°±3°						DRAWN	Zijun_Huang	21.01.13
				SIZE: A4	0.000±0.10	X°X' ±2°								

1

2

3

4

5

6

7

8