




RoHS+HF

NOTE:
1.MATERIAL SPECIFICATION:
1-1.HOUSING:PA66,UL94V-0
1-2.CONTACTS:BRASS H62
2.PLATING SPECIFICATION:
2-1.CONTACTS:TIN PLATED ON CONTACT AREA.
3.MECHANICAL PERFORMANCE:
3-1.INSERTION FORCE: 1KGF/PIN MAX
3-2.REMOVAL FORCE: 3KGF/PIN MIN
3-3.DURABILITY: 50 CYCLES.
4.ELECTRICAL PERFORMANCE:
4-1. RATED CURRENT : 10A
RATED VOLTAGE : 250V
4-2.INSULATION RESISTANCE: 1000MΩ MIN
CONTACT RESISTANCE : 30mΩ MAX
4-3.WITHSTANDING VOLTAGE:1500V AC
5.ENVIRONMENTAL PERFORMANCE:
OPERATING TEMPERATURE: -40°C~+90°C.
6.PACKAGE SPEC:TRAY
7.P/N:
A1 A2201 W 0 1-2 20 1 X X 0
SERIES NO:
CONNECTOR:
W-WAFER
ANGLE:
0-180°
TYPE:
1-TYPE 1
ROW NO:
2-DOUBLE ROW
COLOR:
K-WHITE
PLATING:
C-BRIGHE TIN
TERMIPOINT:
1-DIP
PIN Q'PY:
16

REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE:	NAME	DATE	PART.NO:	DWG.NO:		
A0	NEW RELEASE	21.01.13		LINEAR	ANGLES	1:1						
A1	PART NUMBER RENEWAL	23.10.07		0.0±0.35	X°REF±6°	APPROVED	Wang_jr	23.10.07	A2201W01-2201XX0	ENDE05	WanLian Technology Co., Ltd	
			UNIT:mm	0.00±0.25	X°±3°	DESIGNER	Han_Gao	23.10.07	TITLE:			
			SIZE: A4	0.000±0.10	X°X'±2°	DRAWN	Zijun_Huang	23.10.07	PITCH 2.20mm 180° 立插带扣 汽车连接器		REV: A1	SHEET: 1/1