




The product using material and processing must conform to the "WI-PZ-001"HSF technical standard control requirements

RoHS+HF

NOTE:
1.MATERIAL SPECIFICATION:
1-1.HOUSING:PA66,UL94V-0
1-2.CONTACTS:BRASS H62
2.PLATING SPECIFICATION:
2-1.CONTACTS:TIN PLATED ON CONTACT AREA.
3.MECHANICAL PERFORMANCE:
3-1.INSERTION FORCE: 1KGF/PIN MAX
3-2.REMOVAL FORCE: 3KGF/PIN MIN
3-3.DURABILITY: 50 CYCLES.
4.ELECTRICAL PERFORMANCE:
4-1. RATED CURRENT : 10A
RATED VOLTAGE : 250V
4-2.INSULATION RESISTANCE: 1000MΩ MIN
CONTACT RESISTANCE : 30mΩ MAX
4-3.WITHSTANDING VOLTAGE:1500V AC
5.ENVIRONMENTAL PERFORMANCE:
OPERATING TEMPERATURE: -40°C~+90°C.
6.PACKAGE SPEC:TRAY
7.P/N:

A1 **A2201** **W** **9-2** **12** **1** **X** **X** **0**
SERIES NO: COLOR: K-WHITE
CONNECTOR: PLATING: C-BRIGHE TIN
W-WAFER
ANGLE: 9-90°
ROW NO: 2-DOUBLE ROW
PIN Q' PY: 02~40 TERMIPOINT: 1-DIP

REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO: A2201W9-2121XX0	DWG.NO: ENDE05	 WanLian Technology Co., Ltd
A0	NEW RELEASE	21.01.13		LINEAR	ANGLES	APPROVED	Wang_jr	23.10.08			
A1	PART NUMBER RENEWAL	23.10.08		0.0±0.35	X°REF±6°	DESIGNER	Han_Gao	23.10.08			
			UNIT:mm	0.00±0.25	X°±3°	DRAWN	Zijun_Huang	23.10.08	TITLE: PITCH 2.20mm 90° 卧插带扣 汽车连接器		
			SIZE: A4	0.000±0.10	X°X' ±2°						
										REV: A1	

REV: A1 SHEET: 1/1