



NOTE:

1.MATERIAL SPECIFICATION:
1-1.HOUSING: PA66

2.ELECTRICAL PERFORMANCE:
2-1.CURRENT RATING: 9A
2-2.CONTACT RESISTANCE: 30 mΩ MAX
2-3.INSULATION RESISTANCE: 1000MΩ Min
2-4.DIELECTRIC WITHSTANDING : 1500V

3.ENVIRONMENTAL PERFORMANCE:
3-1.OPERATING TEMPERATURE: -25°C~+85°C.

4.PACKAGE SPEC: PE BAG

5.P/N:

C4201 H 2 M-1 03 X X

SERIES NO: _____

CONNECTOR: _____

H-HOUSING

2-TYPE CODE _____

MALE FEMALE: _____

M-MALE

ROW NO: _____

1-SINGLE ROW

HOUSING:
1-UL94V-0
2-UL94V-2

COLOR:
A-BLACK
S-NATURE

PIN Q'PY:
03PIN

REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART.NO:	DWG.NO:		
AO	NEW RELEASE	21.11.17		LINEAR	ANGLES	APPROVED	Wang_jr	21.11.17	C4201H2M-103XX	ENDE05		
				0.0±0.35	X°REF±6°	CHECK	Han_Gao	21.11.17	TITLE: Pitch 4.2mm Male 单排 中间长两端短 Housing		REV: A0	SHEET: 1/1
			UNIT:mm	0.00±0.25	X°±3°	DRAWN	Zijun_Huang	21.11.17				
			SIZE: A4	0.000±0.10	X°X' ±2°							