



11202H00-NPX-HF
 ① ② ③④ ⑤
 ① Series No.
 ② H90 : Side Contact
 H00 : Up Contact
 ③ No. of Circuits
 ④ X: Product color (A--Y)
 A: Black type
 ⑤ HF: Halogen Free

Circuits	Dimensions		
	A	B	C
2P	--	2.60	3.10
3P	2.40	3.80	4.30
4P	3.60	5.00	5.50
5P	4.80	6.20	6.70
6P	6.00	7.40	7.90
7P	7.20	8.60	9.10
8P	8.40	9.80	10.30
9P	9.60	11.00	11.50
10P	10.80	12.20	12.70
11P	12.00	13.40	13.90
12P	13.20	14.60	15.10
13P	14.40	15.80	16.30
14P	15.60	17.00	17.50
15P	16.80	18.20	18.70

Specifications:
 Rated Voltage : 50V AC/DC
 Rated Current : 2.0A AC,DC
 Withstand Voltage :500V AC/minute
 Contact Resistance : 20mΩ(MAX.)
 Insulation Resistance : 100MΩ(MIN.)
 Temperature Range : -25°C~+85°C
 The product using material and processing must conform to the *WI-PZ-142* HSF technical standard control requirements



Part No.	Material	Color
11202H00-NP-HF	LCP, UL94V-0	Natural(White)
11202H00-NPA-HF	LCP, UL94V-0	Black

REV.	REVISION RECORD	DATE	
C1	HN1404140043	14. 04. 14	
C2	HN1412180212	14. 12. 18	
C3	HR1603110029	16. 03. 11	
C4	HN2009300276	20. 09. 30	

GENERAL TOLERANCES		SCALE:	NAME	DATE
LINER	ANGLES	1:1		
0.0±0.25	X° REF±6°	APPROVED	李卫华	20.09.30
0.00±0.15	X° ±3°	DESIGNER	李卫华	20.09.30
0.000±0.08	X° X'±2°	DRAWN	陈佳龙	20.09.30

PART. NO.: 11202H00-NPX-HF
 DWG. NO.: ENDE05
 TITLE: 1.20mm Pitch W-T-B Connector

JCTC®
 TERMINAL&CONNECTORS
 REV: C4 SHEET: 1/1