



SECTION A-A



SECTION B-B



SECTION C-C

Note: 11254TOP-XX-NK

0A--Gold-flash 0B--2μ" 0C--3μ" 0D--4μ" 0E--5μ" 5A--Gold-flash 5B--2μ" 5C--3μ" 5D--4μ" 5E--5μ"
 0F--10μ" 0G--15μ" 0H--30μ" 0I--50μ" 5F--10μ" 5G--15μ" 5H--30μ" 5I--50μ"
 2E--Tin-plated

The product using material and processing must conform to the "WI-PZ-142" HSF technical standard control requirements

Part No	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
11254TOP-2E-NK	AWG #28~#32	1.00mm(max)	Phosphor Bronze	Tin-plated 60u"	20,000 pcs
11254TOP-0X-NK	AWG #28~#32	1.00mm(max)	Phosphor Bronze	Gold-Plated on contact area	20,000 pcs
11254TOP-5X-NK	AWG #28~#32	1.00mm(max)	Phosphor Bronze	Gold Plated on Overall.	20,000 pcs

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES	SCALE:	NAME	DATE	PART. NO:
				1:1			
C0	换图框发行	13.03.05	 LINEAR ANGLES 0.0±0.25 X° REF±6°	APPROVED	 18.04.18	JCTC® 胜蓝科技股份有限公司 TERMINAL&CONNECTORS 东莞市富智达电子科技有限公司	DWG. NO:
C1	新增电镀规格	15.03.17		0.00±0.15 X° ±3°			DESIGNER
C2	TN1609190147	16.09.19	UNIT: MM	DRAWN	伍文聪	18.04.18	REV: C3
C3	TR1804180051	18.04.18	SIZE: A4	TITLE: MX1.25端子		SHEET: 1/1	